·ı|ı.ı|ı. cısco

Cisco Aironet 1530 Series Outdoor Access Point

Compact Outdoor Wireless

- Most compact carrier-grade outdoor access point/mesh/bridge: 186 cubic in (3.0 liter), 5 lb (2.3 kg)
- 2.4- and 5-GHz radios (802.11b/g/n, 802.11a/n)
- 802.11n range and performance with MIMO technology
- Gigabit Ethernet 10/100/1000 WAN and LAN
- ports
- Controller-based or autonomous operationPowered via PoE or separate DC input
- IP67 enclosure with operating temperature range of -22° to 149°F (-30° to +65°C)

Cisco Aironet 1530I

- Integrated antennas
- 2.4 GHz: 3x3 MIMO, 3 spatial streams
- 5 GHz: 2x3 MIMO, 2 spatial streams
- Ultra low profile
- Cisco Aironet 1530E
- External antennas
- 2.4 and 5 GHz: 2x2 MIMO, 2 spatial streams
- Supports dual-band or single-band antennas
- Versatile RF coverage with external antennas



Sleek, Innovative, Flexible, Proven

As carrier-grade Wi-Fi becomes a critical small-cell element in nextgeneration mobile networks, operators are requesting new access point designs that can pack a punch in a small form factor. The Cisco[®] Aironet[®] 1530 Series Outdoor Access Points incorporate a low-profile design that is aesthetically pleasing, yet they can withstand the most rugged outdoor conditions. Cisco brings engineering innovation to the platform with unique Cisco Flexible Antenna Port technology that allows the same antenna ports to be used either for dual-band antennas to reduce the antenna footprint or for single-band antennas to optimize radio coverage. This flexibility allows antenna changes to

be made on the fly, and saves on sparing costs. And the Cisco Aironet 1530 Series brings all the same robust Wi-Fi features that operators have come to expect from Cisco, including radio resource management, BandSelect to automatically take advantage of the 5-GHz band, and VideoStream for high-quality video performance over Wi-Fi. Only Cisco delivers all of these features in a hardened outdoor access point that is ideal for any urban setting.

Compact, Place-Anywhere Design

Enterprise customers are also looking to expand their wireless coverage and Figure 1. provide seamless network access from indoor to outdoor areas. The Cisco with Solar

Aironet 1530 Series Outdoor Access Points are small enough and light enough to be unobtrusively mounted on street light poles or building facades. The integrated antenna version is just 9 x 7 x 4 inches (23 x 17 x 10 cm) and weighs 5 pounds (2.3 kg). A solar shield/cover option is also available, and can be painted to match its surroundings to allow the access point to be even less noticeable (Figure 1).





Innovative, Integrated, and External Antenna Options

The Cisco Aironet 1530l Outdoor Access Point includes a dual-band, integrated antenna radome. This antenna has three omnidirectional antenna elements with antenna gains of 3 dBi (2.4 GHz) and 5 dBi (5 GHz). More information, including antenna patterns, can be found in the Cisco Aironet Antennas and Accessories Guide: http://www.cisco.com/en/US/products/hw/wireless/ps469/index.html.

The innovatively designed Cisco Aironet 1530E Outdoor Access Point is designed with antenna Cisco Flexible Antenna Port technology, which can support either dual-band or single-band antennas on the same platform and is configurable via software. When configured for dual-band ports, the Aironet 1530E uses the bottom two antenna ports to connect to dual-band omnidirectional or directional antennas. Alternatively, and for additional radio coverage flexibility, the Aironet 1530E can be software-configured, enabling two separate 2.4-GHz and two 5-GHz antenna ports (Figure 2). This flexibility allows customers to use high-gain directional antennas for backhaul on 5 GHz while deploying omnidirectional antennas for access on 2.4 GHz. Refer to the Cisco Aironet 1530 Series Ordering Guide for the latest information on supported antennas.



Figure 2. Cisco Aironet 1530E with Flexible Antenna Port Antenna Technology

Flexible, High-Performance

The Cisco Aironet 1530 Series Outdoor Access Points offer a flexible, highly secure, and scalable platform that can be deployed as part of the <u>Cisco Unified Wireless Network</u> or as a standalone, autonomous solution. The Cisco Aironet 1530 Series provides high-performance device access through improved radio sensitivity and range with 802.11a/b/g/n multiple-input multiple-output (MIMO) technology, with two or three spatial streams and up to 300-Mbps data rates. The Aironet 1530 Series can be deployed in the following configurations:

- Access point: Either in controller-based or standalone operation, provides Wi-Fi connectivity concurrently to clients on both 2.4-GHz and 5-GHz radios.
- Mesh network: as dedicated backhaul or universal access, the 5-GHz radio is used for wireless network connections to adjacent mesh nodes.
- Bridging: Provides point-to-point, high-capacity data links, as well as point-to-multipoint bridging for campuses.
- Workgroup bridge: Enables LAN mobility, such as on a vehicle.
- Serial backhaul: Extends linear mesh with two colocated Aironet 1530 Series access points connected via the LAN port (Figure 3).



Figure 3. Serial Backhaul Using Two Cisco Aironet 1530 Series Access Points

Centrally Managed Network

Central management and troubleshooting of the Cisco outdoor wireless access points help prevent costly maintenance service calls to outdoor locations. Cisco Prime[™] Infrastructure works in conjunction with the Cisco Aironet access points and Cisco wireless LAN controllers to configure and manage the wireless networks. With Cisco Prime Infrastructure, network administrators have a single solution for RF prediction, policy provisioning, network optimization, troubleshooting, security monitoring, and wireless LAN system management. Wireless network security is also a part of a unified wired and wireless solution. Cisco wireless network security offers the highest level of network security, helping ensure that data remains private and secure and that the network is protected from unauthorized access.

Product Specifications

Table 1 lists the specifications for the Cisco Aironet 1530 Series.

Table 1. Cisco Aironet 1530 Series Product Speci	fications
--	-----------

Item	Specification			
Part Numbers	Cisco Aironet 1530I (internal antennas) and 1530E (external antennas) Outdoor Access Points			
	• AIR-CAP1532I-A-K9	AIR-CAP1532E-A-K9		
	• AIR-CAP1532I-B-K9	AIR-CAP1532E-B-K9		
	• AIR-CAP1532I-C-K9	AIR-CAP1532E-C-K9		
	• AIR-CAP1532I-D-K9	AIR-CAP1532E-D-K9		
	• AIR-CAP1532I-E-K9	AIR-CAP1532E-E-K9		
	• AIR-CAP1532I-F-K9	AIR-CAP1532E-F-K9		
	• AIR-CAP1532I-H-K9	AIR-CAP1532E-H-K9		
	• AIR-CAP1532I-K-K9	AIR-CAP1532E-K-K9		
	• AIR-CAP1532I-M-K9	AIR-CAP1532E-M-K9		
	• AIR-CAP1532I-N-K9	AIR-CAP1532E-N-K9		
	• AIR-CAP1532I-Q-K9	AIR-CAP1532E-Q-K9		
	• AIR-CAP1532I-R-K9	AIR-CAP1532E-R-K9		
	• AIR-CAP1532I-S-K9	AIR-CAP1532E-S-K9		
	• AIR-CAP1532I-T-K9	AIR-CAP1532E-T-K9		
	• AIR-CAP1532I-Z-K9	AIR-CAP1532E-Z-K9		
	Cisco SMARTnet [®] Service f	for the Cisco Aironet 1530 Series Access Points		
	Refer to the Service part numbers available on Cisco Commerce Workspace for available service offerings.			
	Not all regulatory domains ha Price List.	we been approved. As they are approved, the part numbers will be available on the Global		

Item	Specification					
802.11n and Related Capabilities	 1530I: 3x3 MIMO with 3 spatial streams (2.4 GHz) and 2x3 MIMO with 2 spatial streams (5 GHz) 1530E: 2x2 MIMO with 2 spatial streams (2.4 GHz) and 2x2 MIMO with 2 spatial streams (5 GHz) 20-MHz (2.4 and 5 GHz) and 40-MHz (5 GHz only) channels PHY data rates up to 300 Mbps Packet aggregation: A-MPDU (Tx/Rx) 802.11 dynamic frequency selection (DFS) Cyclic shift diversity (CSD) support 					
Data Rates	802.11a: 6, 9	, 12, 18, 24, 36, 48, and 54	Mbps			
Supported	802.11b/g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps					
	802.11n data	rates (2.4 and 5 GHz):				
	MCS Index ¹	Gl ² = 800 ns		GI = 400 ns		
		20-MHz Rate (Mbps)	40-MHz Rate (Mbps)	20-MHz Rate (Mbps)	40-MHz Rate (Mbps)	
	0	6.5	13.5	7.2	15	
	1	13	27	14.4	30	
	2	19.5	40.5	21.7	45	
	3	26	54	28.9	60	
	4	39	81	43.3	90	
	5	52	108	57.8	120	
	6	58.5	121.5	65	135	
	7	65	135	72.2	150	
	8	13	27	14.4	30	
	9	26	54	28.9	60	
	10	39	81	43.3	90	
	11	52	108	57.8	120	
	12	78	162	86.7	180	
	13	104	216	115.6	240	
	14	117	243	130	270	
	15	130	270	144.4	300	
	16	19.5		21.7		
	17	39		43.3		
	18	58.5		65		
	19	78		86.7		
	20	117		130		
	21	156		173.3		
	22	175.5		195		
	23	195		216.7		
	MCS 16-23 available on 1530I on 2.4 GHz only.					

¹ MCS Index: The Modulation and Coding Scheme (MCS) index determines the number of spatial streams, the modulation, the coding rate, and data rate values.

² GI: A guard interval (GI) between symbols helps receivers overcome the effects of multipath delays.

Item	Specification
Frequency Range	-A Domain:
and 20-MHz	• 2.412 to 2.462 GHz; 11 channels
Operating Channels	• 5.280 to 5.320 GHz; 3 channels
	• 5.500 to 5.560 GHz; 4 channels
	• 5.680 to 5.700 GHz; 2 channels
	• 5.745 to 5.825 GHz; 5 channels
	-B Domain:
	• 2.412 to 2.462 GHz: 11 channels
	• 5.180 to 5.240 GHz; 4 channels
	• 5 260 to 5 320 GHz 4 channels
	• 5 500 to 5 560 GHz; 4 channels
	 5 680 to 5 720 GHz; 3 channels
	5.745 to 5.825 GHz; 5 channels
	• 5.745 to 5.625 GHZ; 5 channels
	• 2.412 to 2.462 GHz; 11 channels
	• 5.745 to 5.865 GHz; 7 channels
	-E Domain:
	• 2.412 to 2.472 GHz; 13 channels
	• 5.500 to 5.580 GHz; 5 channels
	• 5.660 to 5.700 GHz; 3 channels
	-F Domain:
	• 2.412 to 2.472 GHz; 13 channels
	• 5.745 to 5.805 GHz, 4 channels
	-H Domain:
	• 2.412 to 2.472 GHz; 13 channels
	• 5.745 to 5.825 GHz; 5 channels
	-K Domain:
	• 2.412 to 2.462 GHz; 11 channels
	• 5.280 to 5.320 GHz; 3 channels
	• 5.500 to 5.620 GHz; 7 channels
	• 5.745 to 5.805 GHz; 4 channels
	-M Domain
	• 2.412-2.472 GHz; 13 channels
	• 5.500-5.580 GHz; 5 channels
	• 5.660-5.700 GHz; 3 channels
	• 5.745-5.805 GHz; 4 channels
	-N Domain:
	• 2.412 to 2.462 GHz: 11 channels
	• 5 745 to 5 825 GHz: 5 channels
	-Q Domain
	• 2 412 to 2 472 GHz ⁻ 13 channels
	5 5 500 to 5 700 GHz; 11 channels
	-R Domain:
	• 2 412 to 2 472 GHz 12 chappels
	• 5 260 to 5 220 GHz; 4 channels
	5 560 to 5 700 GHz; 2 chappels
	• 5.000 to 5.700 GHz, 5 that these
	• 5.745 to 5.825 GHZ; 5 channels
	• 2.412 to 2.472 GHz; 13 channels
	• 5.500 to 5.700 GHz; 11 channels
	• 5.745 to 5.825 GHz; 5 channels
	-T Domain:
	• 2.412 to 2.462 GHz; 11 channels

Item	Specification	annala		
	• 5.500 to 5.580 GHz; 5 cha	anneis		
	• 5.660 to 5.700 GHz; 3 channels			
	• 5.745 to 5.825 GHz; 5 channels			
	-Z Domain:			
	• 2.412 to 2.462 GHz; 11 channels			
	• 5.500 to 5.580 GHz; 5 cha	annels		
	• 5.660 to 5.700 GHz; 3 cha	anneis		
	• 5.745 to 5.825 GHz; 5 cha	annels		
Note: These values var	y by regulatory domain. Refer to	o the product documentation fo	or specific details for each regul	atory domain.
Maximum Number of	2.4 GHz		5 GHz	
Nonoverlapping	• 802.11b/g:		• 802.11a:	
Channels	 20 MHz: 3 		 20 MHz: 16 	
	• 802.11n:		• 802.11n:	
	 20 MHz: 3 		 20 MHz: 16 	
			 40 MHz: 8 	
Note: These values var	y by regulatory domain. Refer t	o the product documentation fo	or specific details for each regul	atory domain.
Receive Sensitivity	1530	1530	1530E	1530E
	802 11b (Complementary	802 11g (non HT20)	802 11b (Complementary	802 11g (non HT20)
	Code Keying [CCK])	-95 dBm @ 6 Mbps	Code Keying [CCK])	-93 dBm @ 6 Mbps
	-97 dBm @ 1 Mbps	-92 dBm @ 9 Mbps	-96 dBm @ 1 Mbps	-90 dBm @ 9 Mbps
	-94 dBm @ 2 Mbps	-90 dBm @ 12 Mbps	-93 dBm @ 2 Mbps	-88 dBm @ 12 Mbps
	-92 dBm @ 5.5 Mbps	-87 dBm @ 18 Mbps	-91 dBm @ 5.5 Mbps	-85 dBm @ 18 Mbps
	-90 dBm @ 11 Mbps	-84 dBm @ 24 Mbps	-89 dBm @ 11 Mbps	-82 dBm @ 24 Mbps
		-81 dBm @ 36 Mbps		-82 dBm @ 36 Mbps
		-78 dBm @ 48 Mbps		-76 dBm @ 48 Mbps
		-75 dBm @ 54 Mbps		-73 dBm @ 54 Mbps
2.4 GHz	1530		1530E	
	802.11n (HT20)		802.11n (HT20)	
	-95 dBm @ MCS0		-93 dBm @ MCS0	
	-90 dBm @ MCS1		-88 dBm @ MCS1	
	-87 dBm @ MCS2		-85 dBm @ MCS2	
	-84 dBm @ MCS3		-82 dBm @ MCS3	
	-81 dBm @ MCS4		-79 dBm @ MCS4	
	-78 dBm @ MCS5		-76 dBm @ MCS5	
	-75 dBm @ MCS6		-73 dBm @ MCS6	
	-74 dBm @ MCS7		-72 dBm @ MCS7	
	-90 dBm @ MCS8		-90 dBm @ MCS8	
	-85 dBm @ MCS9		-85 dBm @ MCS9	
	-82 dBm @ MCS10		-82 dBm @ MCS10	
	-79 dBm @ MCS11		-79 dBm @ MCS11	
	-76 dBm @ MCS12		-76 dBm @ MCS12	
	-73 dBm @ MCS13		-73 dBm @ MCS13	
	-70 dBm @ MCS14		-70 dBm @ MCS14	
	-69 dBm @ MCS15		-69 dBm @ MCS15	
	-90 dBm @ MCS16			
	-85 dBm @ MCS17			
	-82 dBm @ MCS18			
	-79 dBm @ MCS19			
	-76 dBm @ MCS20			
	-73 dBm @ MCS21			
	-70 dBm @ MCS22			
	-69 dBm @ MCS23			
1				

Item	Specification					
5 GHz	1530		1530E			
	802.11a (non HT20)		802.11a (non HT20)			
	-94 dBm @ 6 Mbps			-92 dBm @ 6 Mbps		
	-91 dBm @ 9 Mbps		-89 dBm @ 9 Mbps			
	PO dBm @ 12 Mbps		-87 dBm @ 12 Mbns			
	-05 dBm @ 12 Mbps			84 dBm @ 18 Mbps		
	22 dBm @ 24 Mbps			-84 dBm @ 18 Mbps		
				-81 dBm @ 24 Mbps		
	-ou dBm @ 30 Mbps			-78 dBm @ 36 Mbps	-78 dBm @ 36 Mbps	
	-77 dBm @ 54 Mbps			-75 dBm @ 54 Mbps		
	1530	1530		1530E	1530E	
	802.11n (HT20)	802.11n (HT40)	802.11n (HT20)	802.11n (HT40)	
	-94 dBm @ MCS0	-91 dBm @ MC	CS0	-92 dBm @ MCS0	-89 dBm @ MCS0	
	-89 dBm @ MCS1	-86 dBm @ MC	CS1	-87 dBm @ MCS1	-84 dBm @ MCS1	
	-86 dBm @ MCS2	-83 dBm @ MC	CS2	-84 dBm @ MCS2	-81 dBm @ MCS2	
	-83 dBm @ MCS3	-80 dBm @ MC	CS3	-81 dBm @ MCS3	-78 dBm @ MCS3	
	-80 dBm @ MCS4	-77 dBm @ MC	CS4	-78 dBm @ MCS4	-75 dBm @ MCS4	
	-77 dBm @ MCS5	-74 dBm @ MC	285	-75 dBm @ MCS5	-72 dBm @ MCS5	
	-74 dBm @ MCS6	-71 dBm @ MC	286	-72 dBm @ MCS6	-69 dBm @ MCS6	
	-73 dBm @ MCS7	-70 dBm @ MC	287	-/1 dBm @ MCS/	-68 dBm @ MCS7	
	-91 dBm @ MCS8	-88 dBm @ MC	258	-89 dBm @ MCS8	-86 dBm @ MCS8	
	-86 dBm @ MCS9	-83 dBm @ MC	59	-84 dBm @ MCS9	-81 dBm @ MCS9	
	-83 dBm @ MCS10	-80 dBm @ MC	2810	-81 dBm @ MCS10	-78 dBm @ MCS10	
	-80 dBm @ MCS11	-77 dBm @ MC	2511	-78 dBm @ MCS11	-75 dBm @ MCS11	
	-77 dBm @ MCS12	-74 dBm @ MC	2812	-75 dBm @ MCS12	-72 dBm @ MCS12	
	-74 dBm @ MCS13	-71 dBm @ MC	2813	-72 dBm @ MCS13	-69 dBm @ MCS13	
	-71 dBm @ MCS14	-68 dBm @ MC	2014	-69 dBm @ MCS14	-66 dBm @ MCS14	
	-70 dBm @ MCS15	-67 dBm @ MC		-68 dBm @ MCS15	-65 dBm @ MCS15	
Maximum Transmit	2.4 GHz		5 GHz			
	• 802.11b (CCK)		• 802.11	• 802.11a		
	 27 dBm with 2 antenna 20 dBm with 2 antenna 	S	° 27 di	Sm with 2 antennas		
	 29 dBm with 3 antenna 902 11a (non LIT duplication) 	S o modo)	• 802.111	n (H120) Sm with 2 ontonnoo		
	• 802.11g (non H1 duplicat	e mode)	• 27 0	• 27 dBm with 2 antennas		
	 27 dBm with 2 antenna 20 dBm with 2 antenna 	s	• 002.111	• 802.11n (H140)		
	 29 UBIT WIT 5 antenna 802 11p (HT20) 	5	· 2/ ut	 27 dBm with 2 antennas 		
	• 002.1111 (11120)	c				
	 29 dBm with 3 antenna 	 27 dBm with 3 antennas 29 dBm with 3 antennas 				
	Note: The maximum power a		, chonnol and	according to individual cour	the regulations. Befor to the	
	product documentation for sp	ecific details.	y channel and		illy regulations. Refer to the	
Maximum Equivalent	1530I: 32 dBm (2.4 and 5 GH	lz)				
Isotropically	1530E: Tx power plus externa	al antenna gain.				
Radiated Power (FIRP)	wer Note: The maximum EIRP will vary by channel and according to individual country regulations. Refer			lations. Refer to the product		
()	documentation for specific details.					
3G/LTE/WiMAX Co-Location	3G/LTE/WiMAX signal rejection: 33-45 dB. Refer to product documentation for specific details.					
Interfaces	WAN port: 10/100/1000BASE	-T Ethernet, aut	osensing (RJ-4	45)		
	LAN port: 10/100/1000BASE	T Ethernet, auto	sensing (RJ-4	5)		
	Management console port (RJ-45) with Reset button DC power input					
	Multicolor LED					
Dimensions	1530l: 9 x 7 x 4 in. (23 x 17 x	10 cm)	Volume: 179 c	cubic in. (2.9 liters)		
(L x W x H)	1530E: 10 x 7 x 4 in. (26 x 17	' x 10 cm)	Volume: 186 c	cubic in. (3.0 liters)		

Item	Specification		
Weight	1530I: 5.0 lb (2.3 kg) 1530E: 5.5 lb (2.5 kg) Wall/pole mounting bracket: 0.5 lb (0.2 kg) Tilt/horizontal mounting bracket: 2.4 lb (1.1 kg)		
Environmental	Operating temperature: -30° to 65°C (-22° to 149°F) ambient; -30° to 55°C (-22° to 131°F) with solar loading (1200 W/m²) Storage temperature: -50° to 85°C (-58° to 185°F) Operating altitude: 10,000 ft (3048 m) Humidity: 0 - 100%, condensing Wind resistance: • Up to 100 mph sustained winds • Up to 140 mph wind gusts		
Environmental Ratings	• IEC 60529 IP67 • Icing protection MIL-STD-810F (13mm) • Corrosion MIL-STD-810F (192 hours) • Solar radiation EN 60068-2-5 (1200 W/m²) • Vibration ANSI_C136.31-2001		
Antenna Gain	 Integrated dual-band, mixed polarized omnidirectional antenna radome (1530i) 3 dBi (2.4 GHz), 5 dBi (5 GHz) External dual-band omnidirectional antennas AIR-ANT2547VG-N (4dBi, 2.4 GHz; 7 dBi, 5 GHz) External dual-band directional antennas AIR-ANT2588P3M-N= (8 dBi, 2.4 and 5 GHz) External single-band antennas 2.4 GHz AIR-ANT2450V-N (5 dBi, omni) AIR-ANT2430V-N (8 dBi, omni) AIR-ANT243P2M-N= (13 dBi, dual polarized patch) 5 GHz AIR-ANT5114P2M-N= (14 dBi, dual polarized patch) For antenna details, please refer to the Antenna webpage: http://www.cisco.com/go/antennas 		
Powering Options	 1530I/1530E 24 to 57 VDC Power over Ethernet (PoE) (802.3at or Cisco Universal PoE [UPoE]) 		
Power Consumption	1530I: < 30 W 1530E: < 25 W		
Compliance	Safety • UL 60950, 2 nd Edition • CAN/CSA-C22.2 No. 60950, 2 nd Edition • IEC 60950, 2 nd Edition • EN 60950, 2 nd Edition Immunity • <= 5 mJ for 6kV/3kA @ 8/20 ms waveform • ANSI/IEEE C62.41 • EN61000-4-5 Level 4 AC Surge Immunity • EN61000-4-4 Level 4 Electrical Fast Transient Burst Immunity • EN61000-4-3 Level 4 Electrical Fast Transient Burst Immunity • EN61000-4-2 Level 2 ESD Immunity • EN61000-4-2 Level 2 ESD Immunity • EN60950 Overvoltage Category IV Radio approvals • FCC Part 15.247, 15.407 • FCC Bulletin OET-65C • RSS-210		

Item	Specification
	• RSS-102
	• AS/NZS 4268.2003
	ARIB-STD 66 (Japan)
	ARIB-STD T71 (Japan)
	• EN 300 328
	• EN 301 893
	EMI and susceptibility
	• FCC part 15.107, 15.109
	• ICES-003
	• EN 301 489-1, -17
	Security
	Wireless bridging/mesh
	 X.509 digital certificates
	 MAC address authentication
	 Advanced Encryption Standard (AES), Temporal Key Integrity Protocol (TKIP)
	Wireless access
	 802.11i, Wi-Fi Protected Access (WPA2), WPA
	 802.1X authentication, including Extensible Authentication Protocol (EAP) and Protected EAP (EAP-PEAP), EAP Transport Layer Security (EAP-TLS), EAP-Tunneled TLS (EAP-TTLS), EAP-Subscriber Identity Module -d (EAP-SIM), and Cisco LEAP
	 VPN pass-through
	• IP Security (IPsec)
	 Layer 2 Tunneling Protocol (L2TP)
	MAC address filtering
Warranty	1 year

Plan, Build, and Run Services for a Seamless Outdoor Experience

Professional services from Cisco and Cisco Advanced Wireless LAN Specialized Partners facilitate a smooth deployment of the next-generation wireless outdoor solution, while tightly integrating it with the wired and indoor wireless networks. With proven methodologies for planning and deploying end-to-end solutions with secure voice, video, and data technologies and years of experience designing and implementing some of the world's most complex enterprise-class wireless networks, our specialists can help you optimize mobile connectivity to transform your business operations.

We work with your IT staff to see that your architecture, physical sites, and operational staff are ready to support Cisco's integrated, next-generation, outdoor wireless solution with the high performance of the 802.11n standard.

Cisco Capital

Financing to Help You Achieve Your Objectives

Cisco Capital can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. Learn more.

For More Information

For more information about Cisco wireless mesh, contact your local account representative or visit: <u>http://www.cisco.com/go/outdoorwireless</u>.

For more information about the Cisco Unified Wireless Network framework, visit: http://www.cisco.com/go/unifiedwireless. For more information about the Cisco about the Cisco 1530 solution, visit: http://www.cisco.com/en/US/products/ps12831/index.html.

For more information about the Cisco service provider Wi-Fi solution, visit: http://www.cisco.com/go/spwifi.

For more information about Cisco Wireless LAN Mobility, visit: http://www.cisco.com/go/mobility.

s



Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore Europe Headquarters Cisco Systems International BV Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA